

# H2586 Series



H2586 series standard precise slip ring, integrated structure design, with through hole 25.4mm , OD86mm , suitable for rotating application which requires a through hole  $\leq 25.4\text{mm}$  ( remark: if need a hole  $< 25.4\text{mm}$ , can add a inner bushing)

## Part No. description


H2586 - Power circuits no. - Signal circuits no. - Eproduct grade

H:through hole slip ring  
2586:ID 25.4mm, OD 86mm

Example:  
0610:6 circuits,10A per circuit  
1220:2circuits,10A per circuit

Example:  
C: standard level  
D:Industrial level  
H:High quality level

Example:  
06S:6circuits signal (0~2A)  
12S:12circuits signal (0~2A)



## Standard Model List

H2586 series model list							
Part no.	Circuits		Length L(mm)	Part no.	Circuits		Length L(mm)
	10A	Signal or 0~5A			10A	Signal or 0~5A	
H2586-02S	0	2	32	H2586-1210-12S	12	12	120
H2586-0210	2	0	32	H2586-1810-06S	18	6	120
H2586-03S	0	3	36	H2586-2410	24	0	120
H2586-0310	3	0	36	H2586-30S	0	30	144
H2586-06S	0	6	48	H2586-0610-24S	6	24	144
H2586-0210-04S	2	4	48	H2586-1210-18S	12	18	144
H2586-0410-02S	4	2	48	H2586-1810-12S	18	12	144
H2586-0610	6	0	48	H2586-2410-06S	24	6	144
H2586-12S	0	12	72	H2586-3010	30	0	144
H2586-0210-10S	2	10	72	H2586-36S	0	36	168
H2586-0310-09S	3	9	72	H2586-0610-30S	6	30	168
H2586-0610-06S	6	6	72	H2586-1210-24S	12	24	168
H2586-0810-04S	8	4	72	H2586-3610	36	0	168
H2586-1010-02S	10	2	72	H2586-42S	0	42	192
H2586-1210	12	0	72	H2586-0610-36S	6	36	192
H2586-18S	0	18	96	H2586-1210-30S	12	30	192
H2586-0210-16S	2	16	96	H2586-48S	0	48	216
H2586-0410-14S	4	14	96	H2586-0610-42S	6	42	216
H2586-0610-12S	6	12	96	H2586-1010-38S	10	38	216
H2586-0810-10S	8	10	96	H2586-1210-36S	12	36	216
H2586-1010-08S	10	8	96	H2586-1810-30S	18	30	216
H2586-1210-06S	12	6	96	H2586-2410-24S	24	24	216
H2586-1410-04S	14	4	96	H2586-60S	0	60	264
H2586-1610-02S	16	2	96	H2586-0610-54S	6	54	264
H2586-24S	0	24	120	H2586-1010-50S	10	50	264
H2586-0410-20S	4	20	120	H2586-1210-48S	12	48	264
H2586-0610-18S	6	18	120	H2586-72S	0	72	312

\*Remark:Circuits can be combined in parallel for bigger current, N circuits of 10A to get N\*10A,such as 2 circuits of 10A in parallel for 20A use. 10A circuits No. and signal circuits ( 5A) No. can be customized based on standard products,pls inquiry Senring for details.

### Technical Specification

Mechanical		Electrical		
Spec	Data	Spec	Data	
Working life	pls refer to product grade table		Power	Signal
Rotating speed	pls refer to product grade table	Rated voltage	0~690VAC/VDC	0~440VAC/VDC
Working temp.	-30°C~80°C	Insulation resistance	≥ 1000mΩ/500VDC	≥ 1000mΩ/500VDC
Work humidity	0~85% RH	Lead wire spec	AWG17# Silver-plated teflon	AWG22# Silver-plated teflon
Contact material	pls refer to produce grade table	Lead wire length	standard 300mm(can be customized)	
Housing material	AL alloy	Dielectric Strength	800VAC@50Hz,60s	
Torque	0.1N.m (+0.03N.m/6circuits)	Electrical noise	<0.01Ω	
IP grade	IP51			

### Product Grade Table

Grade code	Max rotating speed	Working life	Contact material
C:standard	250RPM	20millisons revolutions	precious metal
D:industrial	600RPM	80millisons revolutions	precious metal
H:high quality	1000RPM	150millisons revolutions	gold alloy

### Color code of Lead Wire

ring#	1	2	3	4	5	6	7	8	9	10	11	12
color	BLK	BRN	RED	ORG	YEL	GRN	BLU	PUR	GRY	WHT	PINK	LGT BLU
ring#	13	14	15	16	17	18	19	20	21	22	23	24
color	WHT/BLK	WHT/BRN	WHT/RED	WHT/ORG	WHT/YEL	WHT/GRN	WHT/BLU	WHT/PUR	WHT/GRY	BLK/RED	BLK/BRN	Transparent

Remark:"1" : the first wire from rotor side , H2586-06S wire color sequence: BLK/BRN/RED/ORG/WHT/GRN , 24 color wires as one group , if more than 24wires, repeat as sequence , use number tube to tell group 1#, 2#....