

## UH1256-01 series USB2.0 signal slip ring



Single channel USB2.0 wire+1~24 circuits power/signal

SenRing UH1256-01 series Single channel USB slip ring, hole size 12.7mm, OD56MM, can transmit 1 channel USB2.0 signal when 360° rotating, can be combined to transmit 1~20 circuits power/signal as well as IEEE1394 and various of USB signal. SNU11 series 1 channel USB slip ring has the advantages of stable signal transmission, no packet loss, no string code, small return loss, small insertion loss, etc....

Hole size 12.7mm, suitable for any rotating application which requires a through hole  $\leq 12.7$ mm. SNU11 series USB slip ring is a standard model, stock available for common use. Pls contact the SenRing technician if you have special specification requirements for customization.

### Part No. Description

UH1256-01 - power circuits - signal circuits - Product grade

U:USB Slip Ring

H means through hole

ID:12.7mm OD:56mm

01:1 set of USB cable

Examples:

C:standard

D:industrial

Examples:

0610:6 circuits@10A

1210:12 circuits@10A

Examples:


06S:6 circuits signal@2A(5A options)

12S:12 circuits signal@2A(5A options)

### Examples

UH1256-01-06S: U means USB signal slip ring, H means through hole slip ring, 1256 means hole size:12.7mm, OD56MM, 01 means 1 channel USB2.0, 06 means 6 circuits signal;

UH1256-01-0310-04S: U means USB signal slip ring, H means through hole slip ring, 1256 means hole size 12.7mm, OD56MM, 01 means 1 channel USB2.0, 0310 means 3 circuits current(10A each), 04S means 4 circuits signal;



### Model List

Model	power/signal circuits no.			USB2.0 channels no.	Length l(mm)
	0~2A	power(10A)	power(20A)		
UH1256-01-02S	2	0	0	1	38
UH1256-01-0210	0	2	0	1	38
UH1256-01-08S	8	0	0	1	55
UH1256-01-0810	0	8	0	1	55
UH1256-01-0210-06S	6	2	0	1	55
UH1256-01-0410-04S	4	4	0	1	55
UH1256-01-14S	14	0	0	1	71.5
UH1256-01-1410	0	14	0	1	71.5
UH1256-01-0410-10S	10	4	0	1	71.5
UH1256-01-0810-06S	6	8	0	1	71.5
UH1256-01-20S	20	0	0	1	88.5

\*Remark: Circuits can be combined in parallel for bigger current, N circuits of 10A to get N\*10A, such as 2 circuits of 10A in parallel for 20A use. Pls contact the SenRing salesman if you want to customize USB and power/signal circuit no, or mix other signal.

## Technical Specification of the slip ring

USB cable	1 channels USB2.0	connector	USB 2.0 male ( female optional)	
Mechanical Data		Electrical Data		
spec	data	spec	data	
working life	refer to slip ring grade table		power	signal
Rotating speed	refer to slip ring grade table	voltage range	0~440VAC/VDC	0~440VAC/VDC
working temp.	-30℃~80℃	insulation resistance	≥1000MΩ/500VDC	≥1000MΩ/500VDC
work humidity	0~85% RH	lead wire spec.	AWG17# Silver	AWG22# Silver
contact material	refer to slip ring grade table		-plated teflon	-plated teflon
housing material	aluminum alloy	lead wire length	standard 300mm(can be customized)	
torque	0.1N.m;+0.03N.m/6 circuits	Dielectric Strength	500VAC@50Hz,60s	
material	RoHS certificate	Electrical noise	<0.01Ω	
CE certificate	Yes			

## Grade code

Grade code	Max rotating speed	working life	contact material
C:standard	400RPM	20 millions	precious metal
D:industrial	800RPM	60 millions	gold-gold

## Color Code of Lead Wire

ring #	1	2	3	4	5	6	7	8	9	10	11	12
color	BLK	BRN	RED	ORG	YEL	GRN	BLU	PUR	GRY	WHT	PINK	LGT BLU
ring#	13	14	15	16	17	18	19	20	21	22	23	24
color	WHT/BLK	WHT/BRN	WHT/RED	WHT/ORG	WHT/YEL	WHT/GRN	WHT/BLU	WHT/PUR	WHT/GRY	BLK/RED	BLK/BRN	Transparent

Remark: "1" : the first wire from rotor side , UH1256-01-06S wire color sequence:BLK/BRN/RED/ORG/YEL/GRN , 24 color wires as one group , if more than 24wires, repeat as sequence , use number tube to tell group 1#, 2#....